



NEW FROM SOLAX

X1-BOOST G4



X1-BOOST G4

2.5kW / 3.0kW / 3.3kW / 3.6kW
4.0kW / 4.2kW / 5.0kW / 6.0kW



Features

Superior Performance

- DC Input: 200% oversizing, 16A current, 50V startup voltage
- In-built global MPP scan for higher yield efficiency

User Friendly Monitoring

- 10s level interval of data update(Optional, new WiFi dongle required)
- Quick and easy configuration (WiFi&APP)

Assured Safety & Reliability

- AC/DC built-in Type II SPD (Optional) and I-V curve diagnosis supported
- Optional external RSD (Rapid Shutdown) and integrated DC AFCI protection (Optional)
- In-built export control function

Superb Adaptability

- Home EV Charger and Heat Pump Solution adaptable
- Mass management and broad extension via Datahub
- Master/Slave parallel solution via Modbus supported

Contact Us for More Information

info@solaxpower.com
service@solaxpower.com



www.solaxpower.com Global: +86 571-56260008
AU: +61 1300 476529 UK: +44 2476 586998
DE: +49 6142 4091664 NL: +31 (0) 852 737932

DC INPUT	6000	6000	6600	7200	8000	8000	10000	12000
Max. PV array input power [Wp]	600	600	600	600	600	600	600	600
Max. PV input voltage [V]	50	50	50	50	50	50	50	50
Startup voltage [V]	360	360	360	360	360	360	360	360
Nominal input voltage [V]	40~560	40~560	40~560	40~560	40~560	40~560	40~560	40~560
MPP tracker voltage range [V]						2 / 1		
No. of MPP trackers / String per MPP tracker						16 / 16		
Max. PV input current[A]							22 / 22	
Isc PV Array Short Circuit current [A]								
AC OUTPUT	2500	3000	3300	3680	4000	4200	5000 ^①	6000
Rated AC output power [W]	10.9	13.1	14.4	16	17.4 ^②	18.3	21.7	26.1
Rated AC output current [A]	2750	3300	3630	4048 ^③	4000	4620	5000 ^②	6000
Max. AC output apparent power [VA]	12	14.4	15.8	17.6 ^⑤	17.4 ^④	20.1	21.7 ^③	27.3
Max. AC output current [A]								
Nominal AC voltage / AC voltage range [V] **					220/230/240;90~290			
Nominal AC frequency / AC frequency range [Hz] **					50/60;±5			
Power Factor range					0.8leading~0.8lagging			
THDi (rated power) [%]					<3			
SYSTEM DATA								
Max. Efficiency [%]					98			
Euro. Efficiency [%]					97			
Standby consumption [W] @Night					<3			
Ingress protection					IP66			
Operating ambient temperature range [°C]					-25~60			
Max. operation altitude [m]					4000			
Relative humidity [%]					0~100			
Typical noise emission [dB]					25 ^⑦			
Storage temperature [°C]					-30~70			
Dimensions (W x H x D) [mm]					404x274x146			
Weight [kg]					11			
Cooling concept					Natural cooling			
Communication interfaces					USB/RS485/DRM, Optional: Meter/CT *			
Optional monitoring dongle					Pocket WiFi/LAN/4G			
Display					2 x LED + LCD (16 x 2) / APP			
PROTECTION								
Over / under voltage protection					Yes			
DC isolation protection					Yes			
Monitoring ground fault protection					Yes			
Grid monitoring					Yes			
DC injection monitoring					Yes			
Back feed current monitoring					Yes			
Residual current detection					Yes			
Anti-islanding protection					Yes			
Over temperature protection					Yes			
SPD (DC/AC)					Type II / Type II (Optional)			
Arc-fault circuit interrupter (AFCI)					Optional			
AC auxiliary power supply (APS)					Optional			
DC Switch					Optional			
STANDARD								
Safety					IEC / EN 62109-1 / -2			
EMC					EN61000-6-1 / 2 / 3 / 4, EN61000-3-2 / 3 / 11 / 12			
Certification					IEC61727, EN50549, G98/G99, AS 4777.2, VDE4105, CEI 0-21, VFR, PPDS, TOR			

^① 5000 (4600 for VDE4105, 4999 for AS4777.2) ^② 5000 (4600 for VDE4105, 4999 for AS4777.2) ^③ 21.7 (20 for VDE4105) ^④ 4048 (3680 For G98/G99, TOR and PPDS) ^⑤ 17.6 (16 For G98/G99, TOR and PPDS)

^⑥ For models with internal fan(Optional), typical noise emission is 30 db

^⑦ Not included in the package. Please purchase additionally. ** The AC voltage and the frequency range may vary from different country codes.

* V1.4. Information may be subject to modify without notice.650.00029.00